

구분 모델	F750-1H-AT12	F750-1H-ST12	F750-1H-AT12	F750-2H-ST50	F750-2H-AT50	F750-3H-ST50	F750-3H-AT50	F750-4H-ST120
	150			300		450		600
유량(LPM)	150			300		450		600
최대압력(Bar) (Max Pressure)	8							
전력(Power)	단상(Single Phase) 220V60Hz							
전력소비량 (Watt)	800 W (1 HP)			800 Wx2 (2 HP)		800 Wx3 (3HP)		800 Wx4 (4HP)
탱크재질 (Tank Msterial)	ALUMINIUM	STEEL	ALUMINIUM	STEEL	ALUMINIUM	STEEL	ALUMINIUM	STEEL
탱크용량(L) (Tank Capacity)	12	10	12	50	50	50	50	120
규 격 LxWxH(mm)	300x480x750	500x230x520	450x210x520	600x480x700	700x370x650	600x480x700	700x370x650	1,120x400x760
소음도 (dB)	55 이하 (Less 55)	평균 60 이하 (Less 60dB)						
기본형 (Basic Style)	무소음형 (Noiseless)	외 부 노 출 형 (Be Exposed style)						
옵션형 (Option Style)		바퀴포함 (Wheel)						